

```
pivot_wider(college_long,  
            id_cols = "Year",  
            names_from = "College",  
            values_from = "Adm_Rate")
```

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

```
pivot_wider(college_long,  
            id_cols = "Year",  
            names_from = "College",  
            values_from = "Adm_Rate")
```

names_from indicates a column, the unique values of which will become the new columns

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

```
pivot_wider(college_long,  
            id_cols = "Year",  
            names_from = "College",  
            values_from = "Adm_Rate")
```

names_from indicates a column, the unique values of which will become the new columns

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

values_from tells us what to use to "fill in" the wide section

id_cols tells us which columns we wish to keep as "identifiers". The default is to use everything except "names_from".

```
pivot_wider(college_long,  
            id_cols = "Year",  
            names_from = "College",  
            values_from = "Adm_Rate")
```

<u>Year</u>	College	<u>Adm_Rate</u>
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

names_from indicates a column, the unique values of which will become the new columns

<u>Year</u>	Grinnell	Oberlin
2018	1	2
2019	3	4

values_from tells us what to use to "fill in" the wide section

```
pivot_longer(college_wide,  
             cols = c("Grinnell", "Oberlin"),  
             names_to = "College",  
             values_to = "Adm_Rate")
```

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

```
pivot_longer(college_wide,  
             cols = c("Grinnell", "Oberlin"),  
             names_to = "College",  
             values_to = "Adm_Rate")
```

cols is a vector of all the columns we want to combine into a single new variable. Here, we want "Grinnell" and "Oberlin" to be in a single variable (names_to) called "College"

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

```
pivot_longer(college_wide,  
             cols = c("Grinnell", "Oberlin"),  
             names_to = "College",  
             values_to = "Adm_Rate")
```

cols is a vector of all the columns we want to combine into a single new variable. Here, we want "Grinnell" and "Oberlin" to be in a single variable (names_to) called "College"

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

All of the values located under the columns in cols will go into a single column which we call values_to

```
pivot_longer(college_wide,  
             cols = c("Grinnell", "Oberlin"),  
             names_to = "College",  
             values_to = "Adm_Rate")
```

cols is a vector of all the columns we want to combine into a single new variable. Here, we want "Grinnell" and "Oberlin" to be in a single variable (names_to) called "College"

Year	Grinnell	Oberlin
2018	1	2
2019	3	4

Year	College	Adm_Rate
2018	Grinnell	1
2019	Grinnell	3
2018	Oberlin	2
2019	Oberlin	4

All of the values located under the columns in cols will go into a single column which we call values_to